

VRP-4DLi



Flow	114 l/min / 4 CFM
Vacuum Level	2 Pa / 15 mikrony
Motor Power	0,32 kW (0,44 KM)
Compression Stages	2
Power Supply	18 V
Motor Speed at 50 Hz	3800 rpm
Noise Level	65 dB
Inlet Connection	1/4", 3/8" SAE
Oil Capacity	0,26 l
Oil Type	mineral, viscosity: 46 mm ² /s
Dimensions	316 x 112 x 242 mm
Weight	6,25 kg
Protection Class	IP20
Operating Temperature	5 - 40°C
Storage Temperature	-10 - 50°C
Minimum Oil Temperature for Startup	5°C
Shut-Off Valve	yes (manual)
Exhaust Plug Thread	in the handle
Vacuum Gauge	no

VRP-4DLi

Motor type	DC 18 V
Work time	about 50 min (battery 9 Ah)
Packaging	aluminum case

Pictures of some products may vary. Every effort has been made to ensure that the information contained in this catalog is correct. Due to constant technological development, we reserve the right to make changes without notice.

VRP-4DLi

Two-stages wireless vacuum pump VALUE designed for use with HFC and HFO refrigerants (e.g., R32, 1234yf).

Key features:

- Two-stage design
- Lightweight, compact size, high-quality vacuum
- Large oil sight glass for monitoring oil levels
- Forced oil circulation ensuring sealed vane operation and pump cooling
- Lightweight and efficient DC motor
- Spark-free design, suitable for use with R32 and 1234yf refrigerants
- Lithium-ion battery
- gas ballast valve - prevents moisture from entering the pump oil



VRP-4DLi



VRP-4DLi



VRP-4DLi



VRP-4DLi

