



## ENVIRO-DUO

**Item Number 4684605**

The powerful ENVIRO-DUO guarantees a smooth suction and filling process which, thanks to the air-cooled two-piston compressor, is equally stable throughout the entire process. The device is controlled with a button and safely extracts all common refrigerants up to and including A2L class.

- Powerful Compressor
- Oil and maintenance free compressor
- Equipped with overfill protection (80%) and self-cleaning mode
- Easy filter change
- Special compartment for moisture filters
- Factory revision and extensive spare parts available

## Technical Data

<b>Color</b>	green   bare
<b>Connector A</b>	1/4" SAE
<b>Connector B</b>	1/4" SAE
<b>Working Pressure</b>	558 psi
<b>Operating Temperature Range</b>	32 - 104 °F
<b>Number of Pistons</b>	2
<b>Voltage</b>	115V
<b>Frequency</b>	60Hz
<b>Protection Class</b>	protection-class-1
<b>Ingression Protection</b>	IP30
<b>Energy Consumption</b>	0.75 kW
<b>Speed</b>	1,450 rpm
<b>Noise Level</b>	70 dB(A)

<b>Packaging</b>	CardboardBox
<b>Current</b>	5A

## Accessories

4493622	CA-CCL-60	Set of 3 charging hoses with ball valve 1/4" SAE, 60"/150 cm, blue, red & yellow, 1x straight 1/4" SAE, 1x straight with ball valve 1/4" SAE and core depressor
9881276	CCL-60	Set of 3 charging hoses, 1/4"SAE, 60"/150 cm blue, red & yellow, 1x straight 1/4" SAE, 1x bended 1/4" SAE with core depressor
4686959	REF-CYL	Lightweight refrigerant cylinder Capacity: 26.2l, connections: W 21.7 x 1/14"
9884820	K1-9/5	Adapter with gasket for large refrigerant cylinders, 5 pieces Thread: 21.8-14 G x 1/4" SAE
4687475	K1-9-LH/5	Adapter with gasket for flammable gases, 5 pieces Thread: W 21.8-14 G-LH x 1/4" SAE
9881865	10859	Venting hose, yellow, 5 m connection: 1/4" SAE